

Addition to Range

Technical Information

Date: March 2012



## Universal CVT Fluid with LXE® Technology

### For use in ANY belt type CVT

- Suitable for use in **ANY** belt type CVT (continuously variable transmission) application! (When used in Honda applications 32,000km service intervals are recommended)
- Minimizes friction between belts and pulleys which protects against fatigue damage
- Maintains the performance of a continuously variable transmission by providing excellent wear protection
- Imparts both shear and oxidation stability to the fluid
- Remains fluid at low temperatures for excellent operation during winter
- Prevents sludge and varnish build up

LUBEGARD Universal CVT Fluid is also for use in place of: Honda Multimatic Fluid (HMMF), Mercedes Benz CVT 28 & 236.20, Mitsubishi/Hyundai/Kia SP-III, Toyota/Mazda/Daihatsu TC Fluid, Suzuki NS-2/TC, and any other belt type CVT Fluid.

**Motospecs Part #: 749459**

**Lubegard Part #: 67032**

**Product Size 32oz / 946ml**



Information on this sheet is prepared as a customer aid, from reliable information, with the utmost care and should not be used for any other purpose. Motospecs reserves the right to make product or publication changes at any time without notice. © Copyright Motospecs, all rights reserved.

**Australia**  
Ph: 1800 463 646



**New Zealand**  
Ph: 0800 333 125